


Cylinder 3 stage front end with outer cover

****ALLOW 50mm TO REMOVE CAP FOR SERVICING**



*Includes 14mm Pull Out.

CS110033344B19A11

SPECIFICATION		TIPPING CAPACITY : 21-34 TONNES***		
Stage	Diameter	Length	Stroke	Swept Volume
-	-	-	-	-
-	-	-	-	-
OUTER COVER	184	985	-	-
0	136	1325	-	-
1	117	1290	1099	12
2	98	1290	1117	8
3	79	1290	1122	6
Total (+5/-10)			3347	26
Final stroke reduced by	0	Priming Volume		9
Cylinder Mass (Kg)	115	Total Volume (Litres)		35
Maximum Pressure (Bar)	190	Max. first stage thrust		130 KN

***TIPPING CAPACITY AT WORKING PRESSURE

Body Length (BL)		BODY LENGTH (BL)				OH
		4550	4675	4800		
22	43°	22	42°	21	41°	150
27	46°	26	45°	25	44°	450
34	50°	32	49°	31	47°	750

d = 178; r = 750; Working Pressure 150 bar

Tipping angle (T)

Body + payload mass, W (tonne)

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS