


Cylinder 4 stage front end with outer cover

****ALLOW 50mm TO REMOVE CAP FOR SERVICING**



***Includes 11mm Pull Out**

CS150044606B19A11

SPECIFICATION		TIPPING CAPACITY : 37-56 TONNES***		
Stage	Diameter	Length	Stroke	Swept Volume
-	-	-	-	-
OUTER COVER	239	1040	-	-
0	177	1375	-	-
1	155	1340	1125	21
2	136	1340	1147	17
3	117	1340	1162	12
4	98	1340	1167	9
Total (+5/-10)			5818	59
Final stroke reduced by	0	Priming Volume		15
Cylinder Mass (Kg)	217	Total Volume (Litres)		74
Maximum Pressure (Bar)	190	Max. first stage thrust		225 KN

***TIPPING CAPACITY AT WORKING PRESSURE

Body Length (BL)		BODY LENGTH (BL)				OH
		5700	5950	6200		
40	47°	38	45°	37	43°	150
46	50°	44	48°	41	46°	450
56	53°	51	51°	48	48°	750

d = 229; r = 750; Working Pressure 165 bar

Tipping angle (T)

Body + payload mass, W (tonne)

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE. PARTS