


Cylinder 5 stage front end with outer cover

**ALLOW 50mm TO REMOVE CAP FOR SERVICING



*Includes 7mm Pull Out.

CS17L055733B25A15

SPECIFICATION

TIPPING CAPACITY : 33-49 TONNES***

Stage	Diameter	Length	Stroke	Swept Volume
OUTER COVER	248	380	-	-
0	199	1375	-	-
1	176	1340	1120	27
2	155	1340	1137	21
3	136	1340	1147	17
4	117	1340	1162	12
5	98	1340	1167	9
Total (+5/-10)			5733	86
Final stroke reduced by	0	Priming Volume		17.8
Cylinder Mass (Kg)	240	Total Volume (Litres)		103.8
Maximum Pressure (Bar)	190	Max. first stage thrust		200 KN

***TIPPING CAPACITY AT WORKING PRESSURE

The diagram illustrates the geometry of a crane boom. It shows a horizontal boom of diameter d and total length BL . The hook is positioned at a distance $L = BL/2 - OH$ from the boom's center. The body and payload mass W act downwards at the boom's center. The hook offset OH is the horizontal distance from the boom's end to the hook's vertical line.

$d = 229$; $r = 900$; Working Pressure 150 bar

BODY LENGTH (BL)						OH
7000		7500		8000		
37	48°	35	45°	33	42°	150
42	51°	38	47°	36	44°	450
49	53°	43	49°	39	46°	750

Tipping angle (T)
 Body + payload mass, W (tonne)

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS