


Cylinder 5 stage front end with outer cover

**ALLOW 50mm TO REMOVE CAP FOR SERVICING



*Includes 7mm Pull Out.

*Includes Blocked Small Inner.


CS17L056233S25A15D

SPECIFICATION

TIPPING CAPACITY : 33-47 TONNES***

Stage	Diameter	Length	Stroke	Swept Volume
OUTER COVER	248	480	-	-
0	199	1475	-	-
1	176	1440	1220	30
2	155	1440	1237	23
3	136	1440	1247	18
4	117	1440	1262	14
5	98	1440	1267	10
Total (+5/-10)			6233	95
Final stroke reduced by	0	Priming Volume		12.7
Cylinder Mass (Kg)	256	Total Volume (Litres)		107.7
Maximum Pressure (Bar)	190	Max. first stage thrust		200 KN

***TIPPING CAPACITY AT WORKING PRESSURE



BODY LENGTH (BL)						OH
7500		8000		8500		
37	49°	34	46°	33	43°	150
41	51°	38	48°	35	45°	450
47	54°	42	50°	39	47°	750

d = 229; r = 900; Working Pressure 150 bar

Tipping angle (θ)

Body + payload mass, W (tonne)

For guidance only;

Higher working pressures and tipping capacities may be possible.

To check your application email - applications@edbro.co.uk


NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer paint to RAL5013
3. Refer to www.edbro.com for;-
 - Bracket details
 - Installation instructions that must be observed
 - Correct oil selection
 - An explanation of tipping capacity

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
 Püßelbürener Damm 244, 49479 Ibbenbüren
 Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
 Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS



CS17L056233S25A15D