


Cylinder 5 stage front end with outer cover

****ALLOW 50mm TO REMOVE CAP FOR SERVICING**



***Includes 7mm Pull Out.**


CS17L058233B19A11

SPECIFICATION

TIPPING CAPACITY : 32-40 TONNES***

Stage	Diameter	Length	Stroke	Swept Volume
OUTER COVER	248	1570	-	-
0	199	1875	-	-
1	176	1840	1620	39
2	155	1840	1637	31
3	136	1840	1647	24
4	117	1840	1662	18
5	98	1840	1667	13
		Total (+5/-10)	8233	125
Final stroke reduced by	0	Priming Volume		25.3
Cylinder Mass (Kg)	336	Total Volume (Litres)		150.3
Maximum Pressure (Bar)	190	Max. first stage thrust		200 KN

***TIPPING CAPACITY AT WORKING PRESSURE



d = 229; r = 900; Working Pressure 150 bar

BODY LENGTH (BL)						OH
10000		10500		11000		
34	48°	33	45°	32	44°	150
37	50°	35	47°	33	45°	450
40	52°	37	49°	35	46°	750

Tipping angle (T)

—Body + payload mass, W (tonne)

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS