


Cylinder 5 stage front end with plain eye



*Includes 9mm Pull Out.


CS17LE56233S70A02

SPECIFICATION

TIPPING CAPACITY : 28-40 TONNES***

Stage	Diameter	Length	Stroke	Swept Volume
-	-	-	-	-
0	199	1475	-	-
1	176	1440	1218	30
2	155	1440	1237	23
3	136	1440	1247	18
4	117	1440	1262	14
5	98	1440	1267	10
Total (+5/-10)			6231	95
Final stroke reduced by		0	Priming Volume	19.3
Cylinder Mass (Kg)		208	Total Volume (Litres)	114.3
Maximum Pressure (Bar)		190	Max. first stage thrust	200 KN

***TIPPING CAPACITY AT WORKING PRESSURE



d = 0; r = 900; Working Pressure 135 bar

BODY LENGTH (BL)						OH
7750		8250		8750		
32	49°	30	46°	28	43°	150
35	52°	32	48°	30	45°	450
40	54°	36	50°	33	47°	750

Tipping angle (T)
Body + payload mass, W (tonne)

NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS