


Cylinder 5 stage front end with plain eye



*Includes 7mm Pull Out.
Last Stage Chrome Plated


CS18LE56983S70A06

SPECIFICATION

TIPPING CAPACITY : 33-42 TONNES***

Stage	Diameter	Length	Stroke	Swept Volume
-	-	-	-	-
0	211	1625	-	-
1	188	1590	1370	38
2	167	1590	1387	30
3	147	1590	1397	24
4	127	1590	1412	18
5	105	1690	1417	12
		Total (+5/-10)	6983	122
Final stroke reduced by	0	Priming Volume		22.7
Cylinder Mass (Kg)	272	Total Volume (Litres)		144.7
Maximum Pressure (Bar)	190	Max. first stage thrust		200 KN

***TIPPING CAPACITY AT WORKING PRESSURE



BODY LENGTH (BL)						OH
8750		9250		9750		
35	49°	33	46°			150
38	51°	36	48°	34	45°	450
42	53°	39	49°	36	48°	750

d = 0; r = 900; Working Pressure 135 bar

For guidance only;

Higher working pressures and tipping capacities may be possible.

To check your application email - applications@edbro.co.uk


NOTES

1. This cylinder is for lifting purposes only and side load conditions should be avoided
2. Cylinder is painted in primer to RAL9005
3. Refer to www.edbro.com for;-
 - Bracket details
 - Installation instructions that must be observed
 - Correct oil selection
 - An explanation of tipping capacity

Edbro

Hoppe-Truck-Hydraulik GmbH & Co.KG
Püßelbürener Damm 244, 49479 Ibbenbüren
Tel.: +49 (0) 5451-50230320, Fax: +49 (0) 5451-50230348
Email: info@hoppe.parts Web: www.hoppe.parts

HTH HOPPE PARTS



CS18LE56983S70A06